Amendment to the Claims

The present listing of claims is as follows:

1.   (Withdrawn) A method for configuring a semiconductor chip, the method comprising:

selecting a private cryptographic key;

selecting a public cryptographic key, wherein the public cryptographic key and the private cryptographic key are not related by a public/private key pair relationship;

embedding the private cryptographic key and the public cryptographic key in a read-only memory on the semiconductor chip; and

storing a second public cryptographic key associated with the private cryptographic key exclusively outside the semiconductor chip.

2.   (Withdrawn) The method of claim 1 wherein the semiconductor chip provides interface processing at a client.

3.   (Cancelled)

4.   (Withdrawn) The method of claim 1 further comprising:

storing the public cryptographic key in a database in association with a serial number associated with the semiconductor chip.

5.   (Withdrawn) The method of claim 1 wherein the private cryptographic key, and the public cryptographic key in the read-only memory are inaccessible to an input/output connection of the semiconductor chip.

6.   (Withdrawn) An article of manufacture comprising:

a first read-only memory structure containing an embedded private cryptographic key, the embedded private cryptographic key being associated with a stored public cryptographic key stored exclusively outside the first read-only memory structure; and

a second read-only memory structure containing an embedded public cryptographic key, wherein the embedded public cryptographic key and the embedded private cryptographic key are not related by a public/private key pair relationship.

7.   (Withdrawn) The article of manufacture of claim 6 wherein the article of manufacture is a semiconductor chip.

8.   (Withdrawn) The article of manufacture of claim 7 wherein the semiconductor chip is capable of providing interface processing at a client.

9.   (Withdrawn) The article of manufacture of claim 8 wherein the first read-only memory structure and the second read-only memory structure are contained within a cryptographic unit of a CPU chip.

10.   (Previously presented) A method for secure communication between a client and a server in a data processing system, the method comprising:

generating a client message at the client;

retrieving an embedded server public key from a read-only memory structure in an article of manufacture in the client, the read-only memory structure having an embedded client private key, the embedded server public key and the embedded client private key not being related by a public/private key pair relationship, the embedded client private key being associated with a client public key stored exclusively outside the client;

encrypting the client message with the embedded server public key; and

sending the client message to the server.

11.   (Previously presented) The method of claim 10 further comprising:

retrieving client authentication data;

retrieving the embedded client private key from a read-only memory structure in an article of manufacture in the client;

encrypting the client authentication data with the embedded client private key; and

storing the encrypted client authentication data in the client message.

12.   (Original) The method of claim 11 further comprising:

retrieving an embedded client serial number from a read-only memory structure in an article of manufacture in the client; and

storing a copy of the embedded client serial number in the client message.

13.   (Previously presented) An apparatus for secure communication between a client and a server in a data processing system, the apparatus comprising:

means for generating a client message at the client;

means for retrieving an embedded server public key from a read-only memory structure in an article of manufacture in the client, the read-only memory structure having an embedded client private key, the embedded server public key and the embedded client private key not being related by a public/private key pair relationship, the embedded client private key being associated with a client public key stored exclusively outside the client;

means for encrypting the client message with the embedded server public key;

and

means for sending the client message to the server.

14. (Previously presented) The apparatus of claim 13 further comprising:

means for retrieving client authentication data;

means for retrieving the embedded client private key from a read-only memory structure in an article of manufacture in the client;

means for encrypting the client authentication data with the embedded client private key; and

means for storing the encrypted client authentication data in the client message.

15. (Original) The apparatus of claim 14 further comprising:

means for retrieving an embedded client serial number from a read-only memory structure in an article of manufacture in the client; and

means for storing a copy of the embedded client serial number in the client message.

16. (Previously presented) A computer program product in a computer-readable medium for use in a data processing system for secure communication between a client and a server, the computer program product comprising:

instructions for generating a client message at the client;

instructions for retrieving an embedded server public key from a read-only memory structure in an article of manufacture in the client, the read-only memory structure having an embedded client private key, the embedded server public key and the embedded client private key not being related by a public/private key pair relationship, the embedded client private key being associated with a client public key stored exclusively outside the client;

instructions for encrypting the client message with the embedded server public key; and instructions for sending the client message to the server.

17.   (Previously presented) The computer program product of claim 16 further comprising:

instructions for retrieving client authentication data;

instructions for retrieving the embedded client private key from a read-only memory structure in an article of manufacture in the client;

instructions for encrypting the client authentication data with the embedded client private key; and

instructions for storing the encrypted client authentication data in the client message.

18.   (Original) The computer program product of claim 17 further comprising:

instructions for retrieving an embedded client serial number from a read-only memory structure in an article of manufacture in the client; and

instructions for storing a copy of the embedded client serial number in the client message.

19.   (Previously presented) A method for secure communication between a client and a server in a data processing system, the method comprising:

generating a server message at the server;

retrieving information that was requested by the client;

storing the retrieved information in the server message;

retrieving a client public key, wherein the client public key corresponds to an embedded client private key in a read-only memory structure in an article of manufacture in the client, and the client public key is stored exclusively outside the client;

encrypting the server message with the client public key; and

sending the server message to the client.

20.   (Previously presented) The method of claim 19 further comprising:

retrieving server authentication data;

retrieving a server private key;

encrypting the server authentication data with the server private key; and

storing the encrypted server authentication data in the server message.

21.   (Previously presented) An apparatus for secure communication between a client and a server in a data processing system, the apparatus comprising:

means for generating a server message at the server;

means for retrieving information that was requested by the client;

means for storing the retrieved information in the server message;

means for retrieving a client public key, wherein the client public key corresponds to an embedded client private key in a read-only memory structure in an article of manufacture in the client, and the client public key is stored exclusively outside the client;

means for encrypting the server message with the client public key; and

means for sending the server message to the client.

22.   (Original) The apparatus of claim 21 further comprising:

means for retrieving server authentication data;

means for retrieving a server private key;

means for encrypting the server authentication data with the server private key;

and

means for storing the encrypted server authentication data in the server message.

23.   (Previously presented) A computer program product in a computer-readable medium for use in a data processing system for secure communication between a client and a server, the computer program product comprising:

instructions for generating a server message at the server;

instructions for retrieving information that was requested by the client;

instructions for storing the retrieved information in the server message;

instructions for retrieving a client public key, wherein the client public key corresponds to an embedded client private key in a read-only memory structure in an article of manufacture in the client, and the client public key is stored exclusively outside the client;

instructions for encrypting the server message with the client public key; and

instructions for sending the server message to the client.

24.   (Original) The computer program product of claim 23 further comprising:

instructions for retrieving server authentication data;

instructions for retrieving a server private key;

instructions for encrypting the server authentication data with the server private

key; and

instructions for storing the encrypted server authentication data in the server

message.

25.   (Previously presented) A method for secure communication between a client and a server in a data processing system, the method comprising:

receiving a client message from the client;

retrieving a server private key;

decrypting the client message with the server private key;

retrieving a client serial number from the decrypted client message; and

retrieving a client public key that is associatively stored with the retrieved client serial number, wherein the client public key corresponds to an embedded client private key in a read-only memory structure in an article of manufacture in the client and is stored exclusively outside the client;

wherein the read-only memory structure has an embedded server public key, the embedded server public key and the embedded client private key not being related by a public/private key pair relationship.

26.   (Original) The method of claim 25 further comprising:

retrieving encrypted client authentication data from the client message;

decrypting the client authentication data with the retrieved client public key; and

verifying the decrypted client authentication data.

27.   (Previously presented) An apparatus for secure communication between a client and a server in a data processing system, the apparatus comprising:

means for receiving a client message from the client;

means for retrieving a server private key;

means for decrypting the client message with the server private key;

means for retrieving a client serial number from the decrypted client message; and

means for retrieving a client public key that is associatively stored with the retrieved client serial number, wherein the client public key corresponds to an embedded client private key in a read-only memory structure in an article of manufacture in the client and is stored exclusively outside the client;

wherein the read-only memory structure has an embedded server public key, the embedded server public key and the embedded client private key not being related by a public/private key pair relationship.

28.   (Original) The apparatus of claim 27 further comprising:

means for retrieving encrypted client authentication data from the client message;

means for decrypting the client authentication data with the retrieved client public key; and

means for verifying the decrypted client authentication data.

29.   (Previously presented) A computer program product in a computer-readable medium for use in a data processing system for secure communication between a client and a server, the computer program product comprising:

instructions for receiving a client message from the client;

instructions for retrieving a server private key;

instructions for decrypting the client message with the server private key;

instructions for retrieving a client serial number from the decrypted client message; and

instructions for retrieving a client public key that is associatively stored with the retrieved client serial number, wherein the client public key corresponds to an embedded client private key in a read-only memory structure in an article of manufacture in the client and is stored exclusively outside the client;

wherein the read-only memory structure has an embedded server public key, the embedded server public key and the embedded client private key not being related by a public/private key pair relationship.

30.   (Original) The computer program product of claim 29 further comprising:

instructions for retrieving encrypted client authentication data from the client message;

instructions for decrypting the client authentication data with the retrieved client public key; and

instructions for verifying the decrypted client authentication data.

31.   (Previously presented) A method for secure communication between a client and a server in a data processing system, the method comprising:

receiving a server message from the server;

retrieving an embedded client private key from a read-only memory structure in an article of manufacture in the client, the embedded client private key being associated with a client public key stored exclusively outside the client; and

decrypting the server message with the embedded client private key.

32.   (Original) The method of claim 31 further comprising:

retrieving encrypted server authentication data from the server message;

retrieving an embedded server public key from a read-only memory structure in an article of manufacture in the client; and

decrypting the server authentication data with the embedded server public key; and

verifying the decrypted server authentication data.

33.   (Original) The method of claim 32 further comprising:

retrieving requested information from the server message; and

in response to a determination that the decrypted server authentication data was verified, processing the requested information.

34.   (Previously presented) An apparatus for secure communication between a client
and a server in a data processing system, the apparatus comprising:

    means for receiving a server message from the server;

    means for retrieving an embedded client private key from a read-only memory
structure in an article of manufacture in the client, the embedded client private key being
associated with a client public key stored exclusively outside the client; and

    means for decrypting the server message with the embedded client private key.

35.   (Original) The apparatus of claim 34 further comprising:

    means for retrieving encrypted server authentication data from the server
message;

    means for retrieving an embedded server public key from a read-only memory
structure in an article of manufacture in the client; and

    means for decrypting the server authentication data with the embedded server
public key; and

    means for verifying the decrypted server authentication data.

36.   (Original) The apparatus of claim 35 further comprising:

    means for retrieving requested information from the server message; and

    means for processing the requested information in response to a determination
that the decrypted server authentication data was verified.

37.   (Previously presented) A computer program product in a computer-readable medium for use in a data processing system for secure communication between a client and a server, the computer program product comprising:

instructions for receiving a server message from the server;

instructions for retrieving an embedded client private key from a read-only memory structure in an article of manufacture in the client, the embedded client private key being associated with a client public key stored exclusively outside the client; and

instructions for decrypting the server message with the embedded client private key.

38.   (Original) The computer program product of claim 37 further comprising:

instructions for retrieving encrypted server authentication data from the server message;

instructions for retrieving an embedded server public key from a read-only memory structure in an article of manufacture in the client; and

instructions for decrypting the server authentication data with the embedded server public key; and

instructions for verifying the decrypted server authentication data.

39.   (Original) The computer program product of claim 38 further comprising:

instructions for retrieving requested information from the server message; and

instructions for processing the requested information in response to a determination that the decrypted server authentication data was verified.

40.   (Withdrawn) The method of claim 1 wherein the embedding step further comprises the embedding of a serial number associated with the semiconductor chip.